Gas Range, 48", 8 Burners

Series 7 Professional
Stainless Steel Natural gas




Size plus power. Eight burners deliver powerful 23,500 BTU heat, with two gas ovens for a combined 7.7 cu ft capacity.

- Top burner heat of 23,500 BTU, for seriously fast boiling
- Expansive 7.7 cu ft total oven capacity across two oven cavities
- Non-tip full-extension shelves in main cavity for safe removal of hot dishes

DIMENSIONS

Height	35 3/4 - 36 3/4"
Width	47 7/8"
Depth	29 1/8"



FEATURES & BENEFITS

Cooktop power

Sealed Dual Flow Burners[™] deliver cooktop power up to 23,500 BTU (NG models) for seriously fast boiling right down to a precise 140°F full surface simmer with the gentlest of flames.

Total control

Precise control across high and low settings is delivered through the halo-illuminated cooktop dials. The ovens have true convection and electronic oven control for precise and consistent temperatures.

FISHER & PAYKEL

A sealed cooktop surface coupled with a commercial-style stainless steel finish means your cooktop simply needs a quick wipe to keep it looking good as new.

Instant visibility

Control dials have halo-illumination glowing white - heating up; orange - temperature reached; red - self-cleaning mode. The oven is illuminated by two powerful incandescent lights.

COOKING FLEXIBILITY

The cooktop is designed for easy access to any burner with grates you can smoothly slide pots across. The oven is large enough to hold full size baking sheets.

Consistent broiling

The Gas Range broiler provides an even heat that covers a very large surface area — perfect for browning a fully loaded oven tray.

SPECIFICATIONS

Accessories (sold separately)

Square handle option

AH-R48

Burner ratings

Maximum burner power	23500 BTU
Power back centre	18500BTU
Power back centre (2)	18500BTU
Power back left	18500BTU
Power back right	18500BTU
Power front centre	18500BTU
Power front centre (2)	18500BTU
Power front left	23500BTU
Power front right	23500BTU

QUICK REFERENCE GUIDE > RGV2-488-N_N

Total cooktop power	158000 BTU
Capacity	
Shelf positions (main oven)	5
Shelf positions (second oven)	5
Controls	
Electric circuit	3 wire
Metal illuminated dials	
Gas Requirements	
Fitting and pipe	½ NPT, min. ¾" 🛛 flex line
Supply Pressure (natural gas)	6" to 9" W.C
Oven features	
Auto re-ignition system	
Internal light	
Oven performance	
Main oven - Bake power	28,000 BTU
Secondary oven - Bake power	18,000 BTU
Power requirements	
Amperage	15A
Rated current	15A
Supply frequency	60Hz
Product dimensions	
Depth	29 1/8″

Height 35 3/4 - 36 3/4" Width 47 7/8" **Rangetop features** Sealed range top Vent trim included

•

.

Recommended Back Guards Ventilation			
Combustible situation	BGRV2-3048H		
Minimum CFM	1200		
Non combustible situation	BGRV2-3048 / BGRV2-1248		
Recommended hood	HCB48-12_N (48""		

Safety

ADA compliant	
Full extension telescopic	

Secondary oven features

3/4 Extension racks	2
Electronic oven control	•
Internal light	•

Secondary oven functions

Bake	•
Number of secondary oven	2
Proof	•
SKU	71350

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. ? Fisher & Paykel Appliances Ltd 2020

FISHER & PAYKEL

Other product downloads available at fisherpaykel.com

- ▲ Service & Warranty

- ↓ Installation Guide EN / Guide d'installation FR
- ▲ Data Sheet Gas Range
- ✓ Planning Guide Gas Range



A PEACE OF MIND SALE

24 Hours 7 Days a Week Customer Support

T 1.888.936.7872 Wwww.fisherpaykel.com