FISHER & PAYKEL

PRELIMINARY SPECIFICATION GUIDE

INTEGRATED INSERT RANGEHOOD





OVERVIEW

This integrated insert rangehood seamlessly blends with cabinetry and can be installed in a variety of kitchen layouts. Choose between three fan speeds for effective extraction of steam, grease and odours while energyefficient LED lighting illuminates the cooking surface beautifully. Designed for simple removal, the aluminium filters are easy to clean and dishwasher safe.

MODELS

Integrated Rangehood, 60cm HP60ICSX4

Integrated Rangehood, 90cm, HP90ICSX4

SERIES & STYLE

Series 5 Integrated

ACCESSORIES

- Aluminium filter HP60ICSX4 793597
- Aluminium filter HP90ICSX4 793598
- ③ Recirculation carbon filter 2x 792481

FEATURES

- Seamlessly integrated into kitchen cabinetry for a minimal look
- 2 Effective extraction of cooking steam, grease and odours
- ③ Up to 780m³/hr airflow
- ④ Energy-efficient LED lighting
- $\ensuremath{\textcircled{}}$ Ducted or recirculated options for flexible installation
- 6 Dishwasher-safe aluminium filters are easy to remove
- Choose between three fan speeds
- 8 Responsive push button controls

*Selected markets and models


FISHER & PAYKEL

PRELIMINARY SPECIFICATION GUIDE

INTEGRATED INSERT RANGEHOOD, 60CM

SPECIFICATIONS		
Model No.	HP60ICSX4	
Dimensions	H 338mm x W 492mm x D 277mm	
Diameter of vent connection	150mm	
Weight		
Unpackaged	6.5kg	
Packaged	7.5kg	
Distance above cooktops	Min. 600mm - Max. 750mm from top of cooktop to base of rangehood	
Electrical		
Supply	220-240V, 50Hz	
Connection	10A plug	


PRODUCT DIMENSIONS



ISO VIEW

		mm
A	Overall height of rangehood with ducting adapter (without ducting adapter)	338 285
в	Overall width of rangehood	492
C	Overall depth of rangehood	277
D	Ducting outlet diameter	150

CAVITY DIMENSIONS: STANDARD INSTALLATION



		mm
A	Overall width of the cutout	460
в	Overall depth of the cutout	260

90003060A Date: 15.05.2023 | The models shown in this Preliminary Specification Guide (PSG) may not be available in all markets and are subject to change at any time. Product specifications may vary from those shown. This PSG is superseded and will become obsolete upon launch of the product. This PSG should not be used as installation guidance for any product. Further information is required to safely and correctly install the products featured here. Specific installation guidance will be available with the product on delivery and on our website fisherpaykel.com


FISHER & PAYKEL

PRELIMINARY SPECIFICATION GUIDE

INTEGRATED INSERT RANGEHOOD, 60CM


SPECIFICATIONS		
Model No.	HP90ICSX4	
Dimensions	H 372mm x W 792mm x D 277mm	
Diameter of vent connection	150mm	
Weight		
Unpackaged	6.5kg	
Packaged	7.5kg	
Distance above cooktops	Min. 600mm - Max. 750mm from top of cooktop to base of rangehood	
Electrical		
Supply	220-240V, 50Hz	
Connection	10A plug	

PRODUCT DIMENSIONS



		mm
A	Overall height of rangehood with ducting adapter (without ducting adapter)	372 315
в	Overall width of rangehood	792
©	Overall depth of rangehood	277
D	Ducting outlet diameter	150

CAVITY DIMENSIONS: STANDARD INSTALLATION



		mm
A	Overall width of the cutout	760
в	Overall depth of the cutout	260