QUICK REFERENCE GUIDE > RDV3-366-N

Dual Fuel Range, 36", 6 Burners, Self-cleaning

Series 9 | Professional

Stainless Steel | Natural gas




Get the best of gas and convection technology in this striking range with intuitive touchscreen and specialized cooking functions.

- Guided cooking using your touchscreen makes it simple to cook by food, function or recipe.
- Top burner heat of 23,500 BTU, for seriously fast boiling
- 4.8 cu ft total oven capacity
- Beautiful LED halo-illuminated dials provide information at a glance

DIMENSIONS

Height	35 3/4 - 36 3/4"		
Width	35 7/8"		
Depth	29 1/8"		



FEATURES & BENEFITS

COOK WITH CONFIDENCE

Our touchscreen interface provides an intuitive guided cooking experience that helps deliver perfect results, whether you've been cooking all your life or just starting out. Cook with a favorite method, a hero ingredient, or a go-to cooking function or recipe. The screen tilts for improved ergonomics and optimal visibility while cooking.

Generous capacity

Featuring a large 4.8 cu ft total capacity convection oven, with

enough room to fit a 32 lb turkey and full-size baking sheets.

Cooking Flexibility

No matter what you're cooking, you've got the right heat to get perfect results. Each of the 15 oven functions have been extensively researched and carefully designed to cater to a broad range of dishes and cooking styles. The handy food probe helps you monitor your progress.

Cooktop Power

Sealed dual flow burners deliver cooktop power up to 23,500 BTU for seriously fast boiling, and precise 140°F full surface, low temperature cooking with the gentlest of flames.

Design Quality

This range has craftsmanship in every detail, with real stainless steel, cast-iron grates, and beautifully weighted, halo illuminated dials. Each cavity features incandescent lights and full extension telescopic racks. From the robust legs to the powerful cooktop, this Range is built to last.

Easy to clean

The oven features a self-cleaning function and self-clean proof side racks, which don't need to be removed when using this function.

SPECIFICATIONS

Accessories Adjustable feet covers Branded coin end cap • Accessories (sold separately) Square handle option AH-R36 Burner ratings

Maximum burner power

23500 BTU

QUICK REFERENCE GUIDE > RDV3-366-N

Power back centre	18500BTU	Fitting and pipe	½ NPT, min. %" 🛭 flex line	Warm	•
Power back left	18500BTU	Supply Pressure (natural gas)	6" to 9" W.C		
Power back right	18500BTU			Oven performance	
Power front centre	18500BTU	Oven features		Bake power	4600W
Power front left	23500BTU	Auto re-ignition system	•	Broil	4000 BTU
Power front right	23500BTU	Concealed element	•	Main oven - True convection	2500W
Total cooktop power 1210	121000 BTU	Electronic oven control	•		
		Food probe	•	Power requirements	
Capacity		Full extension telescopic	•	Amperage	30A
Shelf positions	5	Internal light	•	Supply frequency	60Hz
Total capacity	4.8cu ft	Large broil pan	•		
Usable capacity 3.8cu ft	3.8cu ft	Self-clean proof side racks	•	Product dimensions	
		Titanium coated, illuminated	•	Depth	29 1/8"
Cleaning				Height	35 3/4 - 36 3/4"
Easy clean porcelain basepan	•	Oven functions		Width	35 7/8"
Pyrolytic self-clean •	•	Air fry	•		
		Bake	•	Rangetop features	
Controls		Classic bake	•	Sealed range top	•
Dial with illuminated halo	•	Clean	•	Vent trim included	•
Electric circuit	4 wire	Convection Broil	•		
High resolution display	•	Convection bake	•	Recommended Back Guards Ventilation	
Metal illuminated dials	•	Dehydrate	•	Combustible situation	BGRV3-3036H
Multi-language interface	•	Maxi Broil	•	Non combustible situation	BGRV2-3036 / BGRV2-1236
Precise cooking with food	•	Number of functions	15	Recommended hood	HCB36-6_N (36" Professional
Recipe and food based	•	Pastry bake	•		_ ^
Sabbath mode	•	Pizza bake	•	Safety	
Tilting touch screen interface	•	Rapid proof	•	ADA compliant	
Wi-Fi connectivity	•	Roast	•	Full extension telescopic	
		Slow cook	•	. a.i. extension tolescopie	
Gas Requirements		True convection	•		

QUICK REFERENCE GUIDE > RDV3-366-N

Secondary oven features

Food probe

SKU 81898

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. Fisher & Paykel Appliances Ltd 2020

Where applicable:

All appliances use energy, and energy usage typically generates carbon emissions. Fisher & Paykel Appliances' In-use Energy Carbon Emissions Estimate indicates carbon emissions from a product's in-use energy. This is calculated either annually or per cycle, using the product's market-specific energy label energy consumption data multiplied by the carbon emissions factor for energy in your country or region.

Our In-use Energy Carbon Emissions Estimate is designed to assist customers in making informed purchasing decisions when comparing different Fisher & Paykel products. For example, a heat pump dryer typically has a lower In-use Energy Carbon Emissions Estimate than a vented dryer.

Other product downloads available at fisherpaykel.com



User Guide Professional Range EN



Service & Warranty



Guide d'installation FR



Installation Guide EN



Specification Guide Dual Fuel Range



Data Sheet Dual Fuel Range with Backguard BGRV2-1236



Data Sheet Dual Fuel Range with Backguard BGRV2-3036H and Angled Trim



Data Sheet Dual Fuel Range with Backguard BGRV2-3036



Data Sheet Dual Fuel Range



Planning Guide Dual Fuel Range



Planning Guide Professional Style Dial/Handle Accessories

24/7

A PEACE OF MIND SALE

24 Hours 7 Days a Week Customer Support

T 1.888.936.7872 Wwww.fisherpaykel.com