QUICK REFERENCE GUIDE > RS6121WLUK2

# Integrated Refrigerator Freezer, 61cm, Ice & Water

Series 11 | Integrated

Panel Ready | Left hinge



A slim profile, perfect for compact kitchens, or pair it with other Integrated models for generous chilled and frozen storage.

- Keep food fresher for longer by constantly maintaining the ideal temperature with ActiveSmart<sup>™</sup> technology
- Create the perfect climate for each type of food with Variable Temperature Zone: choice of four food modes, Pantry, Fridge, Soft Freeze or Freezer
- Convenient access to fresh, chilled water and ice with internal water dispenser and ice maker
- Customise with your own kitchen cabinetry or purchase our stainless steel door panel and handle accessories

# **DIMENSIONS**

Height 2134mm
Width 603mm
Depth 610mm

#### **FEATURES & BENEFITS**

#### Variable Temperature Zone

Create the perfect climate and store each type of food at optimal temperature and humidity with Variable Temperature Zone, reducing food waste due to spoiling. You have the choice of four food modes: Pantry, Fridge, Soft Freeze or Freezer. Use the Max cold feature for periods of high refrigerator or freezer use, or full grocery loads.

### Pantry Mode

Not everything benefits from cold storage. Pantry Mode (11 to 13°C) is the perfect climate to store foods that benefit from a cool, dark place, including bread, many types of fruit, bananas, avocados, tomatoes, nuts, grains and cereals.

#### SOFT FREEZE MODE

Soft freeze is for food that requires a gentle freeze and quick thawing, perfect for items that will be consumed soon. It allows easy portioning and the ability to heat, cook or serve straight from the compartment, without waiting for it to thaw.

#### ACTIVESMART™ FOODCARE

ActiveSmart™ Foodcare learns how you live. It's technology which understands how you use your refrigerator and adjusts temperature, airflow and humidity inside to help keep food fresher for longer.

#### Internal water dispenser and ice maker

Both the water dispenser and ice maker are located inside this Integrated model, leaving an uninterrupted exterior that blends in seamlessly with surrounding cabinetry. The slimline water dispenser is flush fit in order to maximise internal storage space, with a temperature-controlled flow and an angled water delivery to capture any drips and spills.

#### Complementary Design

Both the 61cm and 76.2cm Integrated Refrigerator Freezers can be installed separately or paired with a Column Refrigerator, Freezer or Wine Column. Customise with your own kitchen cabinetry and handles, or purchase our stainless steel door panel and handle options.

# Design quality

The premium design and finish includes a steel interior lining as well as full extension metal shelf runners for easy access, robust glass shelving and quality hinges designed for daily use.

#### **SPECIFICATIONS**

Accessories (sold separately)	
Door panel stainless steel Left	RD6121WLD
Door panel stainless steel Right	RD6121WRD
Handle kit Contemporary	AHSRD6121W
Handle kit Contemporary	AHD5RD6121W
Handle kit Contemporary	AHD5RD6121WE
Handle kit Contemporary	AHD3RD6121W
Joiner kit	AJ-RS21LF
Toe kick stainless steel	AKR\$12210
Toe kick stainless steel	AKRS13710
Toe kick stainless steel	AKRS18310
Toe kick stainless steel 1981mm	AKRS19810
Toe kick stainless steel 610mm	AKRS06110
Water filter replacement	847200 - FWC3

#### Capacity

QUICK REFERENCE GUIDE > RS6121WLUK2

Volume	342L	LED ceiling lighting	•
Volume freezer	115L	LED lighting	•
Volume refrigerator	227L	LED side lighting	•
		Slide Out Pastry Tray	•
Consumption		SmartTouch interface at	•
Energy rating	D		
Energy usage	205kWh/year	Performance	
In-use energy carbon	40.8kgCO2e/year	ActiveSmart™ Foodcare	•
		Adaptive defrost	•
Features		Dual evaporator	•
Adjustable door shelves	4	Frost free	•
Covered door shelves	1	Humidity control system	•
Door alarm	•	Inverter controlled compressor	•
Gallon door shelves	1	Noise emissions	42dBA
LED bin lighting	•	Noise emissions class	D
LED ceiling lighting	•	Sabbath mode	•
LED side lighting	•	Variable temperature zones	2
SmartTouch interface at	•		
Stackable bottle holders	4	Power requirements	
Ultra slim water dispenser	•	Rated current	10A
		Supply frequency	50Hz
Freezer Features		Supply voltage	230V
Automatic ice maker	•		
Bottle chill	•	Product dimensions	
Door alarm	•	Depth	610mm
Door shelves	1	Height	2134mm
Freezer bins	2	Width	603mm
Freezer trays	1		
Ice Boost	•	Warranty	
LED bin lighting	•	Parts and labour	5 years

Sealed system parts only	5 years	
SKU	26629	

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. Fisher & Paykel Appliances Ltd 2020

# Where applicable:

All appliances use energy, and energy usage typically generates carbon emissions. Fisher & Paykel Appliances' In-use Energy Carbon Emissions Estimate indicates carbon emissions from a product's in-use energy. This is calculated either annually or per cycle, using the product's market-specific energy label energy consumption data multiplied by the carbon emissions factor for energy in your country or region.

Our In-use Energy Carbon Emissions Estimate is designed to assist customers in making informed purchasing decisions when comparing different Fisher & Paykel products. For example, a heat pump dryer typically has a lower In-use Energy Carbon Emissions Estimate than a vented dryer.

QUICK REFERENCE GUIDE > RS6121WLUK2

# Other product downloads available at fisherpaykel.com



Service & Warranty



User Guide Integrated Refrigerator Freezer



Declaration of Conformity Refrigeration with WiFi Capability



Installation Guide Integrated Column Refrigerator Freezer



Water Filter Replacement Instructions & Installation Guide EN



Installation Guide Toe Kick



# A PEACE OF MIND SALE

24 Hours 7 Days a Week Customer Support

T 08000 886 605 Wwww.fisherpaykel.com