

61cm Series 11 Integrated Column Refrigerator

Integrated



<p>Install it separately or pair with another Column for seamless kitchen integration - this model is right hinge with stainless steel interior.*</p>

- Customise with your own kitchen cabinetry or purchase our stainless steel door panel accessory
- ActiveSmart™ technology helps keep food fresher for longer by constantly maintaining the ideal temperature
- Two separate Variable Temperature Zones. Choose from Fridge, Pantry or Chill
- Internal water dispenser for convenient access to fresh, chilled water

DIMENSIONS

Height	2134 mm
Width	603 mm
Depth	610 mm

FEATURES & BENEFITS

Variable Temperature Zones
When it comes to optimal food preservation, one temperature does not fit all. Create the perfect climate for different food and drink types using Variable Temperature Zones. Change a compartment to Fridge, Pantry or Chill Mode for maximum everyday convenience, or change modes for additional capacity when you need it.

Pantry Mode
Not everything benefits from cold storage. Pantry Mode (11 to 13°C) is the perfect climate to store foods that benefit from a cool, dark place, including bread, many types of fruit, bananas, avocados, tomatoes, nuts, grains and cereals.

Internal Water Dispenser
This integrated model features a slimline water dispenser, located on the inside for an uninterrupted exterior. The flush-fit design of the water dispenser maximises internal storage space, allowing the shelves to be adjusted to suit your needs. Enjoy a continuous flow of temperature-controlled chilled water to fill almost any size or shape of vessel.

Mix & Match
Integrated Column Refrigeration gives you the freedom to mix and match refrigerators and freezers based on your needs – or install separately. They can be customised with your kitchen cabinetry for a seamless look, or finished with one of our stainless steel door panels.

Clever Energy
ActiveSmart™ makes your refrigerator more energy efficient – adapting to daily use and cooling and defrosting only when needed. This means it uses the energy it needs without compromising on food care.

Appealing Illumination
Bright LEDs light up the ceiling, shelves, bins and trays in both refrigerator and freezer, creating a welcoming glow in your kitchen at night and using less power than comparable halogen lights.

Design Quality
The premium design and quality finish includes a white or stainless steel interior lining, as well as full-extension metal shelf runners for easy access and robust glass shelving.

SPECIFICATIONS

Accessories (sold separately)	
Door panel stainless steel Left hinge 610mm	RD6121L10D
Door panel stainless steel Right hinge 610mm	RD6121R10D
Handle kit Classic	AHCLRDSF
Handle kit Contemporary round, aluminium	AHSRDSF
Handle kit Contemporary square fine, aluminium	AHD5RDSF
Handle kit Contemporary square fine, black	AHD5RDSFB
Handle kit Professional round flush	AHP3RDSF
Joiner Kit	AJ-RS21LR
Toe kick stainless steel 1067mm	AKRS10710
Toe kick stainless steel 1220mm	AKRS12210
Toe kick stainless steel 1372mm	AKRS13710
Toe kick stainless steel 1524mm	AKRS15210
Toe kick stainless steel 1828mm	AKRS18310
Toe kick stainless steel 1981mm	AKRS19810
Toe kick stainless steel 610mm	AKRS06110
Toe kick stainless steel 762mm	AKRS7610

Capacity	
Total gross capacity	383 L
Volume	351 L
Volume refrigerator	351 L

Connected Features

Alerts and notifications	•
Education and onboarding	•
Remote operation	•
Software updates	•

Consumption

Energy rating	3.5 star
Energy usage	192 kWh/year

Features

Adjustable door shelves	4
Adjustable glass cantilevered shelves	•
Adjustable glass shelves	3
Covered door shelves	1
Door alarm	•
Gallon door shelves	1
LED bin lighting	•
LED ceiling lighting	•
LED side lighting	•
Smart appliance	•
SmartTouch control panel	•
Soft-close fruit and vegetable bins	•
Stackable bottle holders	4

Performance

ActiveSmart™ Foodcare	•
Adaptive defrost	•
Dual evaporator	•
Frost free	•
Humidity control system	•

Inverter controlled compressor	•
Sabbath mode	•
Variable food modes lower compartment	Pantry; Fridge; Chill
Variable temperature zones	2

Power requirements

Rated current	10 A
Supply frequency	50 Hz
Supply voltage	230 V

Product dimensions

Depth	610 mm
Height	2134 mm
Width	603 mm

SKU	26101
-----	-------

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. © Fisher & Paykel Appliances Ltd 2020

Other product downloads available at fisherpaykel.com

↓	DXF
↓	DXF
↓	DWG
↓	Energy Label
↓	Water Filter Replacement Instructions - Parts 847200 and 847201 (English)

↓	Installation Guide - Toe Kick (English)
↓	Installation Guide (English)
↓	Installation Guide (English)
↓	Planning Guide - Assisted Opening Accessory (English)
↓	Planning Guide (English)
↓	Revit
↓	Rhino
↓	Rhino - Door and Contemporary Round Handle
↓	Rhino - Door and Contemporary Square Handle
↓	SketchUp
↓	SketchUp - Door and Contemporary Round Handle
↓	SketchUp - Door and Contemporary Square Handle
↓	User Guide (English)
↓	User Guide (Chinese)

Where applicable:

All appliances use energy, and energy usage typically generates carbon emissions. Fisher & Paykel Appliances' In-use Energy Carbon Emissions Estimate indicates carbon emissions from a product's in-use energy. This is calculated either annually or per cycle, using the product's market-specific energy label energy consumption data multiplied by the carbon emissions factor for energy in your country or region.

Our In-use Energy Carbon Emissions Estimate is designed to assist customers in making informed purchasing decisions when comparing different Fisher & Paykel products. For example, a heat pump dryer typically has a lower In-use Energy Carbon Emissions Estimate than a vented dryer.



A PEACE OF MIND SALE
24 Hours 7 Days a Week Customer Support
T 1300 650 590 [Wwww.fisherpaykel.com](https://www.fisherpaykel.com)