QUICK REFERENCE GUIDE > RS6019S3RH1 Date: 24.04.2024 > 1

Integrated Triple Zone Refrigerator, 60cm, Water

Series 9 | Integrated

Panel Ready | Right Hinge



Pair with the Integrated Triple Zone Freezer for the ultimate kitchen solution - this model features three independent food zones taking cooling flexibility to a new level.

- Three independent food zones, each with adjustable temperature to store different foods
- Panel ready, flush fit design with 4mm gaps and custom height installation
- Convenient access to fresh, chilled water with internal water dispenser
- Easy-to-use touch-control panel and Wi-Fi capability

DIMENSIONS

Height 1870mm
Width 592mm
Depth 576mm

FEATURES & BENEFITS

Three levels of freshness

When it comes to optimal food preservation, one temperature does not fit all. Three independent food zones give you full control over the way you care for food. The Fridge zone has adjustable temperature from 1 to 6°C, while the bottom two compartments can be converted into a Fridge (1 to 6°C), Pantry (11 to 13°C) or Chill zone (-1.5 to 0°C), to best suit different types of food. Adjust temperature for everyday convenience, or to provide additional chilling capacity for special occasions.

Perfect fit

These models fit flush, with only 4mm gaps around them and no visible hinges or grilles. Our Integrated models can be seamlessly hidden behind your cabinetry, or you can purchase our stainless steel door panel.

Mix & Match

These modular refrigerators and freezers can be mixed and matched, with different sizes and finishes. Installed side by side or individually throughout the kitchen, you can create a cooling solution to suit your lifestyle. Customise with your own kitchen cabinetry and handles, or purchase our stainless steel door panel and handle options.

Slimline water dispenser

The slimline water dispenser is located inside this Integrated model, leaving an uninterrupted exterior that blends in seamlessly with surrounding cabinetry. The flush fit design

maximises internal storage space, with a temperature-controlled flow and an angled water delivery to reduce drips and spills.

Clever energy

ActiveSmart™ Foodcare learns how you live. It is technology that understands how you use your refrigerator and adjusts temperature, airflow and humidity inside to help keep food fresher for longer.

Simple installation

Our Integrated products are easy to install, whether you are renovating your kitchen or designing a new one. Adjustable front and rear feet allow for uneven floors alongside adjustable door panels that can be customised to match your kitchen. These models are designed to easily slide into place as separate units – a perfect fit for European design kitchens.

Ease of use

Using the intuitive touch-sensitive control panel, you can easily adjust the temperature to suit. Beautiful to use, the refrigerator door is family safe with a soft-close mechanism.

SPECIFICATIONS

Accessories

Hinge change (from right hinge

Accessories (sold separately)

Door panel stainless steel RD6019 (right & left hinge) Handle kit Contemporary **AHSRDSF** Handle kit Contemporary AHD5RDSF Handle kit Contemporary AHD5RDSFB Handle kit Professional round AHP3RDSF Joiner kit AJRS19LR Toe kick stainless steel AKRS12010 Toe kick stainless steel **AKRS18010** QUICK REFERENCE GUIDE > RS6019S3RH1 Date: 24.04.2024 > 2

Toe kick stainless steel 600mm	AKRS06010	ActiveSmart™ Foodcare	•
Water filter replacement	847200 - FWC3	Adaptive defrost	•
		Frost free	•
Capacity		Humidity control system	•
Volume	306L	Humidity controlled crisper	4
Volume refrigerator	306L	Inverter controlled compressor	•
		Sabbath mode	•
Consumption		Triple evaporator	•
Energy rating	С	Variable food modes	Pantry; Fridge; Chill
Energy usage	114kWh/year	Variable temperature zones	3
Features		Power requirements	
Adjustable door shelves	4	Amperage	10A
Adjustable glass cantilevered	•	Supply frequency	50Hz
Covered door shelves	1	Supply voltage	230VV
Door alarm	•		
Internal water dispenser	•	Product dimensions	
LED bin lighting	•	Depth	576mm
LED ceiling lighting	•	Height	1870mm
LED side lighting	•	Width	592mm
SmartTouch control panel	•		
Stackable bottle holders	2	Warranty	
Water tank capacity	1L	Parts and labour	2 years
		Sealed system parts only	5 years
Installation Dimensions			
Minimum inside width of	600mm		
Minimum internal depth of	600mm	SKU	26212
Minimum internal height of	1880mm		

Performance

specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. ? Fisher & Paykel Appliances Ltd 2020

and model. Under our policy of continuous improvement, these dimensions and

QUICK REFERENCE GUIDE > RS6019S3RH1 Date: 24.04.2024 > 3



24 Hours 7 Days a Week Customer Support

T 08000886605 **W**www.fisherpaykel.com