

Gas Rangetop, 48", LPG

Series 9 | Professional

Stainless Steel | LPG




Eight burners for when you need maximum performance and cooktop space – great for those who love to cook for a crowd.

- Your burners can deliver anything from a high 19,000 BTU heat per burner for fast boiling, to a gentle flame for simmering
- Continuous surface grates designed for pots and pans to move safely across the cooktop

DIMENSIONS

Height	8 5/16"
Width	47 7/8"
Depth	28"



FEATURES & BENEFITS

- Perfect Heat**
Sealed Dual Flow Burners™ deliver rangetop power up to 23,500 BTU (NG models) for seriously fast boiling right down to a precise 140°F full surface simmer with the gentlest of flames.
- Precise Control**
From the highest to the lowest temperatures you get total control with halo-illuminated rangetop dials. A precise full surface simmer is delivered across all burners.

- Cooking Flexibility**
The continuous surface grates are designed for pots and pans to move safely across the rangetop. Full coverage, deep-platform style grates are designed so heat goes directly onto the pot rather than the grates themselves, for a faster boil and energy efficiency.
- Information at a glance**
LED halo control dials provide information at a glance and assist in alerting you if any burners are accidentally left on.

- Easy cleaning**
These rangetops have sealed burners and a single sheet cooking surface which, combined with a commercial-style stainless steel finish and dishwasher-safe grates, allow easy cleaning.

- Complementary Design**
Built to last with distinctive, bold styling, this rangetop is designed to match the Fisher & Paykel Professional style family of appliances.

SPECIFICATIONS

Burner ratings	
Max burner power	Yes
Power back centre	18500BTU
Power back centre (2)	18500BTU
Power back left	18500BTU
Power back right	18500BTU
Power front centre	18500BTU
Power front centre (2)	18500BTU
Power front left	23500BTU
Power front right	23500BTU

- Controls**
Metal illuminated dials •

Performance

Sealed Dual Flow Burners™	8
Simmer on all burners	140°F

Power requirements

Amperage	15A
Supply frequency	60Hz
Supply voltage	120V

Product dimensions

Depth	28"
Height	8 5/16"
Width	47 7/8"

Recommended Back Guards Ventilation

Minimum CFM	1200 BTU
Pro hood	VS48

Warranty








Parts and labour	2 years
------------------	---------

SKU	71385
-----	-------

All appliances use energy, and energy usage typically generates carbon emissions. **Fisher & Paykel Appliances' In-use Energy Carbon Emissions Estimate** indicates carbon emissions from a product's in-use energy. This is calculated either annually or per cycle, using the product's market-specific energy label energy consumption data multiplied by the carbon emissions factor for energy in your country or region.

Our In-use Energy Carbon Emissions Estimate is designed to assist customers in making informed purchasing decisions when comparing different Fisher & Paykel products. For example, a heat pump dryer typically has a lower In-use Energy Carbon Emissions Estimate than a vented dryer.

Other product downloads available at fisherpaykel.com

-  [User Guide](#)
-  [Guide d'utilisation FR](#)
-  [Service & Warranty](#)
-  [Installation Guide](#)
-  [Guide d'installation FR](#)
-  [Data Sheet Gas Rangetop](#)
-  [Planning Guide Gas Rangetop](#)



A PEACE OF MIND SALE
24 Hours 7 Days a Week Customer Support
T 1.888.936.7872 **W** www.fisherpaykel.com

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. Fisher & Paykel Appliances Ltd 2020

Where applicable: