


60cm Series 9 Contemporary Warming Drawer

Contemporary




Serve meals hot and directly from a pre-heated plate thanks to our panel-ready, warming drawer.

- Integrates with surrounding cabinetry for a seamless look
- Space to keep six standard-sized place settings evenly warm
- Easy to clean smooth-glass base
- Six versatile tailored programmes for warming, proofing, dehydrating and slow cooking

DIMENSIONS

Height 140 mm

Width 596 mm
Depth 567 mm



FEATURES & BENEFITS

Complementary Design

This Warming Drawer comes in a stylish black reflective glass finish, for seamless pairing with our Contemporary style ovens.

Multi-Function Flexibility

Choose from six tailored functions, including Rapid Proof for dough proofing and Dehydrate for drying foods like meat, fruit, and herbs. The Slow Cook function is ideal for finishing seared meats, casseroles, stews, and braises.

Precise Control

Our warming drawer delivers quick, even heating, ideal for keeping food warm and low-temperature cooking. You can also use it for resting roasted meat and proofing dough for bread or pizza bases.

Added Convenience

With intuitive touch controls and a handle-free, push-to-open design, our warming drawer gives you the freedom to keep plates or cups warm while you continue to cook.

Easy To Clean

Cleaning and care of the warming drawer is easy. After each use, simply wipe out the smooth glass interior with a damp cloth.

Safe And Sound

With automatic switch-off and delayed start functionality, our warming drawers help keep dishes warm until it is time to serve the main meal.

Sized To Suit

With enough room to gently heat six place settings, 20 cappuccino cups or 42 espresso cups, our 60cm warming drawer is an ideal kitchen companion.

SPECIFICATIONS

Capacity

Cappuccino cups	20
Espresso cups	42
Maximum allowable weight	25 kg
Place settings	6
Usable depth	408 mm
Usable height	98 mm
Usable width	535 mm

Cleaning

- Easy clean smooth-glass base

Controls

- Audio feedback
- Automatic pre-set temperatures

Automatic timers	30', 45', 1h, 2h, 4h, 6h	Adjustable front door panel to align with surrounding cabinetry	•		All appliances use energy, and energy usage typically generates carbon emissions. Fisher & Paykel Appliances' In-use Energy Carbon Emissions Estimate indicates carbon emissions from a product's in-use energy. This is calculated either annually or per cycle, using the product's market-specific energy label energy consumption data multiplied by the carbon emissions factor for energy in your country or region.
Delayed start	•	Depth		567 mm	
Electronic capacitive touch controls	•	Height		140 mm	
On/Off indicator	•	Width		596 mm	
Pre-set heating functions	•				
Push-to-open drawer	•				
Standby mode	•				
Functions		Safety			
Cups	•	Automatic turn off after 12 hours	•		
Dehydrate	•	Full extension slides	•		
Number of functions	6				
Plates	•				
Rapid proof	•				
Slow cook	•				
Warm	•				
Performance					
Heated glass base and fan	•	Other product downloads available at fisherpaykel.com			
Low temperature cooking	•				
Temperature levels	6	↓ DXF			
Temperature range	35°C-85°C	↓ DWG			
		↓ Installation Guide (English)			
		↓ Planning Guide - 60cm Contemporary Stainless Steel (English)			
		↓ User Guide (English)			
Power requirements					
Amperage	10 A	Where applicable:			
Power cord length	1800 mm				
Supply frequency	50 Hz				
Supply voltage	220-240 V				
Product dimensions					