QUICK REFERENCE GUIDE > RGV2-486GD-L\_N

Date: 02.05.2024 > 1

# Gas Range 48", 6 Burners with Griddle, LPG

Series 7 | Professional

Stainless Steel | LPG




A striking addition to your kitchen, with six powerful gas burners and two gas ovens giving you a combined capacity of 7.7 cu ft.

- Top burner heat of 19,000 BTU, for seriously fast boiling
- Expansive 7.7 cu ft total oven capacity across two oven cavities
- Non-tip full-extension shelves in main cavity for safe removal of hot dishes

### **DIMENSIONS**

Height	35 3/4 - 36 3/4"
Width	47 7/8"
Depth	29 1/8"



#### **FEATURES & BENEFITS**

#### Cooktop Power

Sealed Dual Flow Burners™ deliver cooktop power up to 23,500 BTU (NG models) for seriously fast boiling right down to a precise 140°F full surface simmer with the gentlest of flames.

#### Total control

Precise control across high and low settings is delivered through the halo-illuminated cooktop dials. The ovens have true convection and electronic oven control for precise and consistent temperatures.

### Instant visibility

Control dials have halo-illumination glowing white - heating up; orange - temperature reached; red - self-cleaning mode. The oven is illuminated by two powerful incandescent lights.

#### Easy To Clean

A sealed cooktop surface coupled with a commercial-style stainless steel finish means your cooktop simply needs a quick wipe to keep it looking good as new.

## **Cooking Flexibility**

The cooktop is designed for easy access to any burner with grates you can smoothly slide pots across. The oven is large enough to hold full size baking sheets.

#### Design quality

This range has been carefully crafted in every detail from performance to durability using quality materials.

### **SPECIFICATIONS**

#### Accessories (sold separately)

Square handle option AH-R48

## **Burner ratings**

Maximum burner power 19000 BTU Power back centre 13000BTU Power back left 13000BTU Power back right 13000BTU Power front centre 15000BTU Power front left 19000BTU Power front right 15000BTU Power griddle 15000BTU Total cooktop power 103000 BTU

Ca	рa	citv

Shelf positions (main oven)	5
Shelf positions (second oven)	5

#### Controls

Electric circuit	3 wire
Metal illuminated dials	•

### **Gas Requirements**

Fitting and pipe	½ NPT, min. %" 🛭 flex line
Supply Pressure (LPG)	11" to 14" W.C

### Oven features

Auto re-ignition system	
Internal light	

## Oven performance

Main oven - Bake power	22,000 BTU
Secondary oven - Bake power	18,500 BTU

### Power requirements

Amperage	15A
Rated current	15A
Supply frequency	60Hz

#### **Product dimensions**

Depth	29 1/8"
Height	35 3/4 - 36 3/4"
Width	47 7/8"

# Rangetop features

Sealed range top	•
Vent trim included	

### **Recommended Back Guards Ventilation**

Combustible situation	BGRV2-3048H
Minimum CFM	1200
Non combustible situation	BGRV2-3048 / BGRV2-1248
Recommended hood	HCB48-12_N (48"

#### Safety

ADA compliant	•
Full extension telescopic	•

## Secondary oven features

3/4 Extension racks	2
Electronic oven control	•
Internal light	•

### Secondary oven functions

Bake	•
Number of secondary oven	2
Proof	•

SKU	71347

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and

specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. Fisher & Paykel Appliances Ltd 2020

### Where applicable:

All appliances use energy, and energy usage typically generates carbon emissions. Fisher & Paykel Appliances' In-use Energy Carbon Emissions Estimate indicates carbon emissions from a product's in-use energy. This is calculated either annually or per cycle, using the product's market-specific energy label energy consumption data multiplied by the carbon emissions factor for energy in your country or region.

Our In-use Energy Carbon Emissions Estimate is designed to assist customers in making informed purchasing decisions when comparing different Fisher & Paykel products. For example, a heat pump dryer typically has a lower In-use Energy Carbon Emissions Estimate than a vented dryer.

# Other product downloads available at fisherpaykel.com



Service & Warranty



User Guide EN



Installation Guide EN / Guide d'installation FR



Data Sheet Gas Range



Planning Guide Gas Range



# A PEACE OF MIND SALE

24 Hours 7 Days a Week Customer Support

**T** 1.888.936.7872 **W**www.fisherpaykel.com