QUICK REFERENCE GUIDE > OB24SCDEPX1

Oven, 24", 11 Function, Selfcleaning

Series 9 | Contemporary

Stainless Steel




With a subtle black glass finish, this contemporary-style oven has multiple functions to ensure every dish is cooked to perfection.

- Three cubic feet total capacity with eleven oven functions including Aero™ Pastry, Roast and Rapid Proof
- Self-cleaning function breaks down food residue for an easy clean
- Moisture control and even heat distribution thanks to ActiveVent™ and AeroTech technology
- Non-tip, full-extension sliding shelves for safe removal of hot dishes

DIMENSIONS

Height	23 9/16"
Width	23 1/2"
Depth	22 1/4"



FEATURES & BENEFITS

GENEROUS CAPACITY

With a generous sized internal cavity, you can create several dishes at once using multiple shelves.

Perfect Results

Our built-in ovens feature ActiveVent technology for optimized moisture levels, and AeroTech™ for even heat distribution. Get perfect results even when you're using multiple shelves.

Multi-function flexibility

11 functions including Aero™ Pastry, Roast and Rapid Proof mean no matter what you're cooking, you've got the right heat to match.

Seamless Fit

Designed to fit seamlessly in your kitchen, this built-in oven fits flush with cabinetry to minimize gaps and add to a cohesive aesthetic.

Refined Styling

With sophisticated handle styling and elegant black or stainless steel finish, our built-in ovens are designed to match the rest of Fisher & Paykel's kitchen appliance family.

Cleaning Is Simple

The self-clean function breaks down food residue at a very high temperature, leaving a light ash that's easily removed with a damp cloth.

SAFE AND SOUND

The CoolTouch door features triple glazing and a cooling system that ensures it's safe to touch from the outside – protecting both your hands and the surrounding cabinetry.

SPECIFICATIONS

Accessories Step down wire shelf Wired temperature sensor

Accessories (sold separately)

Optional Accessory round	Part 81671
Optional round handle	Part 81645

Capacity

Shelf positions

QUICK REFERENCE GUIDE > OB24SCDEPX1 Date: 02.05.2024 > 2

Self-clean	Total capacity	3cu ft	Rapid proof	•
True Aero Acid resistant graphite enamel Vent bake Pyrolytic self-clean Warm Pyrolytic self-clean Warm Pyrolytic self-clean Warm Pyrolytic self-clean Warm Pyrolytic self-clean Pyro	Usable capacity	2.5cu ft	Roast	•
Acid resistant graphite enamel			Self-clean	•
Pyrolytic self-clean	Cleaning		True Aero	•
Removable oven door Removable oven door Removable oven door inner Removable shelf runners Performance ActiveVent" system - AeroTech" technology - Automatic rapid pre-heat - Automatic rapid pre-heat - Automatic cooking/minute Whisper quiet cooking - Automatic pre-set	Acid resistant graphite enamel	•	Vent bake	•
Removable oven door inner Removable shelf runners - ActiveVent™ system - AeroTech™ technology - Audio feedback - Audio feedback - Broil power - Automatic rapid pre-heat - Automatic rapid pre-heat - Whisper quiet cooking - Automatic pre-set - Celsius/Fahrenheit - Power requirements - Electronic capacitive touch - Amperage - Supply frequency - Supply requency - Supply voltage - 208-240V - Intuitive touchscreen display - Soft close doors - Product dimensions - Turned stainless capacitive - Height - 23 9/16™ - Functions - Width - 23 1/2™ - Aero Bake - Bake - Balanced oven door - Befoll - Catalytic venting system - Maxi Broil - Control panel key lock - Control panel	Pyrolytic self-clean	•	Warm	•
Removable shelf runners - ActiveVent™ system - AeroTech™ technology - December - Audio feedback - Audio feedback - Broil power - Automatic cooking/minute - Whisper quiet cooking - Automatic pre-set - Celsius/Fahrenheit - Power requirements - Electronic capacitive touch - Amperage - 16.6-19.4A - Electronic clock - Supply frequency - 60Hz - Electronic oven control - Supply voltage - 208-240V - Intuitive touchscreen display - Soft close doors - Product dimensions - Turned stainless capacitive - Depth - 22 1/4™ - Height - 23 9/16™ - Functions - Width - 23 1/2™ - Aero Bake - Aero Bake - Balanced oven door - Bake - Balanced oven door - Broil - Catalytic venting system - Maxi Broil - Control panel key lock - Supply coltage - Control gape and the specific panels and the specific panels are specific panels. - ActiveVent™ system - ActiveVent™ system - Adronatic rapid pre-heat - Panel Maxi Broil - Control panel key lock - Supply port cooking - ActiveVent™ system - ActiveNent	Removable oven door	•		
Aero Tech™ technology - Controls Audio feedback Audio feedback Automatic cooking/minute - Automatic pre-set - Celsius/Fahrenheit - Celsius/Fahrenheit - Electronic capacitive touch - Electronic clock - Electronic oven control - Supply requency - Supply voltage - Supply voltage - Supply voltage - Colsius/Fahrenheit - Bepth - B	Removable oven door inner	•	Performance	
Audio feedback	Removable shelf runners	•	ActiveVent™ system	•
Audio feedback Automatic cooking/minute Automatic pre-set Celsius/Fahrenheit Power requirements Electronic capacitive touch Electronic oven control Supply voltage 208-240V Intuitive touchscreen display Soft close doors Turned stainless capacitive Product dimensions Turned stainless capacitive Height 23 1/2" Aero Bake Aero Baril Aero Pastry Bake Balanced oven door Broil Maxi Broil Power requirements Amperage 16.6-19.4A Electronic cook Supply requency 60Hz Supply voltage 208-240V Height 23 1/2" Height 33000W Amperage 16.6-19.4A Electronic oven control Product dimensions Vidth 23 1/2" Height 23 1/2" Aero Bake Aero Pastry ADA compliant ADA compliant ADA compliant ADA control panel key lock Amai Broil			AeroTech™ technology	•
Automatic cooking/minute Automatic pre-set Celsius/Fahrenheit Power requirements Electronic capacitive touch Electronic clock Supply frequency Supply voltage 208-240V Intuitive touchscreen display Soft close doors Turned stainless capacitive Depth Eleight Product dimensions Turned stainless capacitive Height Aero Bake Aero Baroil Aero Pastry Bake Balanced oven door Broil Maxi Broil Catalytic venting system Maxi Broil Amperage 16.6-19.4A Amperage 16.6-	Controls		Automatic rapid pre-heat	•
Automatic pre-set Celsius/Fahrenheit Power requirements Electronic capacitive touch Amperage 16.6-19.4A Electronic clock Supply frequency 60Hz Electronic oven control Supply voltage 208-240V Intuitive touchscreen display Soft close doors Product dimensions Turned stainless capacitive Depth 22 1/4" Height 23 9/16" Functions Aero Bake Aero Broil Aero Pastry Aero Pastry Aero Pastry Bake Balanced oven door Catalytic venting system Maxi Broil Control panel key lock Amperage 16.6-19.4A Power requirements Power requirements 16.6-19.4A Power requirements 16.6-19.4A Power requirements 16.6-19.4A Power requirements 16.6-19.4A Amperage 16.6H Amperage 16.6H Amperage 16.6H Amperage 16.6H	Audio feedback	•	Broil power	3000W
Celsius/Fahrenheit Power requirements Electronic capacitive touch Amperage Supply frequency Supply voltage 208-240V Intuitive touchscreen display Soft close doors Product dimensions Turned stainless capacitive Height Height 23 9/16" Functions Aero Bake Aero Broil Aero Pastry Aero Pastry Bake Balanced oven door Broil Catalytic venting system Maxi Broil Control panel key lock Catalytic venting system Catalytic venting system Catalytic venting system Catalytic venting system Control panel key lock Catalytic venting system Catalytic venting system Control panel key lock	Automatic cooking/minute	•	Whisper quiet cooking	•
Electronic capacitive touch - Amperage - I6.6-19.4A Electronic clock - Supply frequency - Supply voltage - 208-240V Intuitive touchscreen display - Soft close doors - Product dimensions Turned stainless capacitive - Depth - 22 1/4" - Height - 23 9/16" Functions - Width - 23 1/2" Aero Bake - Aero Broil - Safety - ADA compliant - Bake - Balanced oven door - Broil - Catalytic venting system - Maxi Broil - Control panel key lock - Control p	Automatic pre-set	•		
Electronic clock Supply frequency Supply voltage 208-240V Intuitive touchscreen display Soft close doors Product dimensions Turned stainless capacitive Depth 22 1/4" Height 23 9/16" Functions Width 23 1/2" Aero Bake Aero Broil Aero Pastry Aero Pastry Bake Balanced oven door Broil Catalytic venting system Maxi Broil Control panel key lock PORD 208-240V A208-240V A21 1/4" A22 1/4" A23 9/16" A24 Agriculture and accordance and a	Celsius/Fahrenheit	•	Power requirements	
Electronic oven control Intuitive touchscreen display Soft close doors Turned stainless capacitive Depth Height 23 9/16" Functions Aero Bake Aero Broil Aero Pastry Aero Pastry Bake Balanced oven door Broil Catalytic venting system Maxi Broil Control panel key lock	Electronic capacitive touch	•	Amperage	16.6-19.4A
Intuitive touchscreen display Soft close doors Turned stainless capacitive Depth Height 23 9/16" Functions Aero Bake Aero Broil Aero Pastry Aero Pastry Bake Balanced oven door Catalytic venting system Maxi Broil Control panel key lock Control panel key lock	Electronic clock	•	Supply frequency	60Hz
Soft close doors Turned stainless capacitive Depth 22 1/4" Height 23 9/16" Functions Width 23 1/2" Aero Bake Aero Broil Aero Pastry Aero Pastry Bake Balanced oven door Broil Catalytic venting system Maxi Broil Control panel key lock Control panel key lock	Electronic oven control	•	Supply voltage	208-240V
Turned stainless capacitive Depth Height 23 9/16" Functions Width 23 1/2" Aero Bake Aero Broil Safety Aero Pastry Aero Pastry Bake Balanced oven door Broil Catalytic venting system Maxi Broil Control panel key lock	Intuitive touchscreen display	•		
Height 23 9/16" Functions Width 23 1/2" Aero Bake • Safety Aero Pastry • ADA compliant • Bake • Balanced oven door • Broil • Catalytic venting system • Control panel key lock • Control panel key lock	Soft close doors	•	Product dimensions	
Aero Bake Aero Broil Aero Pastry Aero Pastry Bake Balanced oven door Catalytic venting system Maxi Broil Control panel key lock Width 23 1/2" ADA compliant Catalytic venting system Control panel key lock	Turned stainless capacitive	•	Depth	22 1/4"
Aero Bake Aero Broil Aero Pastry Aero Pastry Bake Balanced oven door Catalytic venting system Maxi Broil Control panel key lock			Height	23 9/16"
Aero Broil Aero Pastry Aero Pastry Bake Balanced oven door Catalytic venting system Control panel key lock Control panel key lock	unctions		Width	23 1/2"
Aero Pastry ADA compliant Bake Balanced oven door Catalytic venting system Control panel key lock Control panel key lock	Aero Bake	•		
Bake Balanced oven door Catalytic venting system Control panel key lock Control panel key lock	Aero Broil	•	Safety	
Broil • Catalytic venting system • Maxi Broil • Control panel key lock •	Aero Pastry	•	ADA compliant	•
Maxi Broil • Control panel key lock •	Bake	•	Balanced oven door	•
Solition patient key rook	Broil	•	Catalytic venting system	•
Number of functions 11 Non-tip shelves •	Maxi Broil	•	Control panel key lock	•
	Number of functions	11	Non-tip shelves	•

SKU 82255

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. Fisher & Paykel Appliances Ltd 2020

Where applicable:

All appliances use energy, and energy usage typically generates carbon emissions. Fisher & Paykel Appliances' In-use Energy Carbon Emissions Estimate indicates carbon emissions from a product's in-use energy. This is calculated either annually or per cycle, using the product's market-specific energy label energy consumption data multiplied by the carbon emissions factor for energy in your country or region.

Our In-use Energy Carbon Emissions Estimate is designed to assist customers in making informed purchasing decisions when comparing different Fisher & Paykel products. For example, a heat pump dryer typically has a lower In-use Energy Carbon Emissions Estimate than a vented dryer.

QUICK REFERENCE GUIDE > OB24SCDEPX1 Date: 02.05.2024 > 3

Other product downloads available at fisherpaykel.com



User Guide



Service & Warranty



Data Sheet Oven



A PEACE OF MIND SALE

24 Hours 7 Days a Week Customer Support

T 1.888.936.7872 **W**www.fisherpaykel.com