

# 60cm Series 9 Integrated Triple Zone Refrigerator

Integrated



Pair with the Integrated Triple Zone Freezer for the ultimate kitchen solution – this model features three independent food zones taking cooling flexibility to a new level.

- Three independent food zones, each with adjustable temperature to store different foods
- Panel ready, flush fit design with 4mm gaps and custom height installation
- Convenient access to fresh, chilled water with internal water dispenser
- Easy-to-use touch-control panel and Wi-Fi capability

## DIMENSIONS

Height	1870 mm
Width	592 mm
Depth	576 mm

## FEATURES & BENEFITS

### Three Levels Of Freshness

When it comes to optimal food preservation, one temperature does not fit all. Three independent food zones give you full control over the way you care for food. The Fridge zone has adjustable temperature from 1 to 6°C, while the bottom two compartments can be converted into a Fridge (1 to 6°C), Pantry (11 to 13°C) or Chill zone (-1.5 to 0°C), to best suit different types of food. Adjust temperature for everyday convenience, or to provide additional chilling capacity for special occasions.

### Perfect Fit

These models fit flush, with only 4mm gaps around them and no visible hinges or grilles. Our Integrated models can be seamlessly hidden behind your cabinetry, or you can purchase our stainless steel door panel.

### Mix & Match

These modular refrigerators and freezers can be mixed and matched, with different sizes and finishes. Installed side by side or individually throughout the kitchen, you can create a cooling solution to suit your lifestyle. Customise with your own kitchen cabinetry and handles, or purchase our stainless steel door panel and handle options.

### Slimline Water Dispenser

The slimline water dispenser is located inside this Integrated model, leaving an uninterrupted exterior that blends in seamlessly with surrounding cabinetry. The flush fit design maximises internal storage space, with a temperature-controlled flow and an angled water delivery to reduce drips and spills.

### Clever Energy

ActiveSmart™ Foodcare learns how you live. It is technology that understands how you use your refrigerator and adjusts temperature, airflow and humidity inside to help keep food fresher for longer.

### Simple Installation

Our Integrated products are easy to install, whether you are renovating your kitchen or designing a new one. Adjustable front and rear feet allow for uneven floors alongside adjustable door panels that can be customised to match your kitchen. These models are designed to easily slide into place as separate units – a perfect fit for European design kitchens.

### Ease Of Use

Using the intuitive touch-sensitive control panel, you can easily adjust the temperature to suit. Beautiful to use, the refrigerator door is family safe with a soft-close mechanism.

## SPECIFICATIONS

### Accessories (included)

Hinge change (from right hinge to left hinge)

### Accessories (sold separately)

Door panel set stainless steel

Handle kit Classic

Right & Left hinge RD6019

AHCLRDSF

Handle kit Contemporary round, aluminium	<b>AHSRDSF</b>
Handle kit Contemporary square fine, aluminium	<b>AHD5RDSF</b>
Handle kit Contemporary square fine, black	<b>AHD5RDSFB</b>
Joiner Kit	<b>AJRS19LR</b>
Toe kick stainless steel 1200mm	<b>AKRS12010</b>
Toe kick stainless steel 1800mm	<b>AKRS18010</b>
Toe kick stainless steel 600mm	<b>AKRS06010</b>
Water filter replacement	<b>847200 - FWC3</b>

Adjustable glass cantilevered shelves	•
Covered door shelves	<b>1</b>
Door alarm	•
LED bin lighting	•
LED ceiling lighting	•
LED side lighting	•
Smart appliance	•
SmartTouch control panel	•
Stackable bottle holders	<b>2</b>

Rated current	<b>10 A</b>
Supply frequency	<b>50 Hz</b>
Supply voltage	<b>230 V</b>

**Product dimensions**

Depth	<b>576 mm</b>
Height	<b>1870 mm</b>
Width	<b>592 mm</b>

**Capacity**

Total gross capacity	<b>330 L</b>
Volume	<b>306 L</b>
Volume refrigerator	<b>306 L</b>

**Installation Dimensions**

Minimum inside width of cabinetry frame	<b>600 mm</b>
Minimum internal depth of cabinetry	<b>600 mm</b>
Minimum internal height of cabinetry	<b>1880 mm</b>

SKU 27051

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. © Fisher & Paykel Appliances Ltd 2020

**Connected Features**

Alerts and notifications	•
Education and onboarding	•
Remote operation	•
Software updates	•

**Performance**

ActiveSmart™ Foodcare	•
Adaptive defrost	•
Frost free	•
Humidity control system	•
Humidity controlled crisper bins	<b>4</b>
Inverter controlled compressor	•
Sabbath mode	•
Triple evaporator	•
Variable food modes	<b>Pantry; Fridge; Chill</b>
Variable temperature zones	<b>3</b>

**Other product downloads available at fisherpaykel.com**

- [↓ DXF](#)
- [↓ DXF](#)
- [↓ Archicad](#)
- [↓ DWG](#)
- [↓ DWG](#)
- [↓ Installation Guide \(English\)](#)
- [↓ Revit](#)
- [↓ Rhino](#)
- [↓ Rhino - Custom Panel](#)
- [↓ Rhino - Door and Classic Round Handle](#)

**Consumption**

Energy consumption	<b>131kWh/year</b>
Energy rating	<b>4 ticks</b>
In-use energy carbon emissions estimate	<b>49.8kgCO2e/year</b>

**Features**

Adjustable door shelves	<b>4</b>
-------------------------	----------

**Power requirements**

- ↓ Rhino - Door and Contemporary Round Handle
- ↓ Rhino - Door and Professional Round Flush Handle
- ↓ Rhino - Door and Square Fine Black Handle
- ↓ Rhino - Door and Square Fine Handle
- ↓ SketchUp
- ↓ SketchUp - Custom Panel
- ↓ SketchUp - Door and Classic Round Handle
- ↓ SketchUp - Door and Contemporary Round Handle
- ↓ SketchUp - Door and Professional Round Flush Handle
- ↓ SketchUp - Door and Square Fine Black Handle
- ↓ SketchUp - Door and Square Fine Handle

**Where applicable:**

All appliances use energy, and energy usage typically generates carbon emissions. **Fisher & Paykel Appliances' In-use Energy Carbon Emissions Estimate** indicates carbon emissions from a product's in-use energy. This is calculated either annually or per cycle, using the product's market-specific energy label energy consumption data multiplied by the carbon emissions factor for energy in your country or region.

Our In-use Energy Carbon Emissions Estimate is designed to assist customers in making informed purchasing decisions when comparing different Fisher & Paykel products. For example, a heat pump dryer typically has a lower In-use Energy Carbon Emissions Estimate than a vented dryer.



**A PEACE OF MIND SALE**  
24 Hours 7 Days a Week Customer Support  
T +65 6741 0777 W [www.fisherpaykel.com](http://www.fisherpaykel.com)