FISHER & PAYKEL

SPECIFICATION GUIDE

INTEGRATED SINGLE DISHDRAWER™ DISHWASHER, TALL, SANTISE SERIES 9, INTERGRATED STYLE





OVERVIEW

Designed to fit your full-sized dinner plates, this DishDrawer™ can be placed anywhere in your kitchen, integrating seamlessly

MODELS

Integrated Single DishDrawer™ Dishwasher, Tall, Sanitise
Panel Ready
DD60STI9

Integrated Single DishDrawer™ Dishwasher, Tall, Sanitise
Panel Ready
DD60SHTI9

SERIES & STYLE

Series 9 Integrated Style

FEATURES

- ② Six wash program, from delicate to heavy to suit any load
- Additional Quick wash, Sanitise and Extra Dry options
- Can be positioned at bench height, for easy of loading and minimal bending.
- $\begin{tabular}{ll} \hline (s) & Flexible racking can be folded down to fit bigger \\ dishes & \\ \hline \end{tabular}$
- Spray arm sensing, for a more reliable wash
- With soft-close mechanism and knock-to-pause function

ACCESORIES

- ① Optional contemporary square handle kit
- Optional contemporary round handle kit
- Optional stainless steel door kit
- 4 Cutlery basket
- S Knife clip and multipurpose clip

FISHER & PAYKEL


SPECIFICATION GUIDE

INTEGRATED SINGLE DISHDRAWER™ DISHWASHER, TALL, SANTISE SERIES 9, INTERGRATED STYLE

SPECIFICATIONS


Model No.	DD60STI9, DD60SHTI9	
Dimensions	H 454mm x W 599mm x D 571mm	
Electrical		
Supply	220-240V, 50Hz	
Service	4.2A	
Receptacle	3 pin earthing-type	
Plumbing		
Supply	3/4" BSP (GB20) to suit flat washer	
Pressure	Water softener models: max. 1 MPa (145 psi), min. 0.1 MPa (14.5 psi) Non-water softener models: max. 1 MPa (145 psi), min. 0.03 MPa (4.3 psi)	

PLUMBING AND ELECTRICAL



Service outlet at rear extends both sides, hoses and cords can be routed to either or both sides

PRODUCT DIMENSIONS




PROFILE VIEW

	mm
Overall height of chassis*	454
Overall width of chassis*	599
© Depth of chassis*	553
Minimum height of custom front panel	452
© Width of custom front panel	596 - 615
© Depth of custom front panel	16 - 20
Height of gap below front panel	2
(H) Depth of open drawer	527

^{*}Does not include custom front panel

ISO VIEW

CAVITY DIMENSIONS: STANDARD INSTALLATION



	mm
Overall height	456
B Overall width	600
© Minimum overall depth of cavity*	579

*Assumes a door panel thickness of 19mm