

24" Series 9 Contemporary Warming Drawer

Contemporary



- Keep plates warm until ready to serve; rapid proof or slow cook to perfection. Pair with an oven for matching Contemporary design.
- A companion product, designed to match with other Contemporary style Fisher & Paykel products
 - Space to keep six standard-sized dinner place settings evenly warm
 - Easy to clean smooth-glass base
 - Six versatile tailored programmes for warming, proofing, dehydrating and slow cooking

DIMENSIONS

Height	5 1/2 "
Width	23 7/16 "
Depth	22 5/16 "

FEATURES & BENEFITS

- Complementary Design**
Our Warming Drawer comes in either a stylish black reflective glass or brushed stainless steel, for seamless pairing with our matching ovens.
- Multi-Function Flexibility**
Choose from six tailored functions including Rapid Proof, Dehydrate and Slow Cook.
- Easy To Clean**
Cleaning and care of the Warming Drawer is simple. After each use, just wipe out the smooth glass interior with a damp cloth.
- Easy To Use**
Handle-free, push-to-open with capacitive touch controls, our Warming Drawer gives you the freedom to keep plates or cups warm while you continue to cook.
- Precise Control**
With fast and even heating, our warming drawer is great for keeping food warm and low temperature cooking, as well as resting after a traditional roast in the oven and proofing dough.
- Safe And Sound**
With Automatic switch-off and Delayed start functionality, our warming drawers help keep dishes warm until it is time to serve the main meal.

SPECIFICATIONS

Capacity	
Cappuccino cups	20
Espresso cups	42

Maximum allowable weight	55 lbs
--------------------------	--------

Cleaning

- Easy clean smooth-glass base

Controls

- Audio feedback
- Automatic timers30', 45', 1h, 2h, 4h, 6h
- Electronic capacitive touch controls
- On/Off indicator
- Pre-set heating functions
- Push-to-open drawer
- Standby mode

Functions

- Cups
- Dehydrate
- Number of functions6
- Plates
- Rapid proof
- Slow cook
- Warm

Performance

- Heated glass base and fan
- Low temperature cooking
- Temperature levels6
- Temperature range95°F-185°F

Power Requirements	
Amperage	10 A
Power outlet	3-prong grounding-type
Supply frequency	60 Hz
Supply voltage	120 V

Product Dimensions	
Adjustable front door panel to align with surrounding cabinetry	•
Depth	22 5/16 "
Height	5 1/2 "
Width	23 7/16 "

Safety	
Automatic turn off after 12 hours	•
Full extension slides	•

SKU	82110
-----	-------

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. © Fisher & Paykel Appliances Ltd 2020

Other product downloads available at fisherpaykel.com

- [↓](#) DWG
- [↓](#) DXF
- [↓](#) Archicad

- [↓](#) Installation Guide (English)
- [↓](#) Revit
- [↓](#) Rhino
- [↓](#) Right To Repair Declaration (English, Canadian French)
- [↓](#) SketchUp
- [↓](#) User Guide (English)
- [↓](#) User Guide (Canadian French)

Where applicable:

All appliances use energy, and energy usage typically generates carbon emissions. **Fisher & Paykel Appliances' In-use Energy Carbon Emissions Estimate** indicates carbon emissions from a product's in-use energy. This is calculated either annually or per cycle, using the product's market-specific energy label energy consumption data multiplied by the carbon emissions factor for energy in your country or region.

Our In-use Energy Carbon Emissions Estimate is designed to assist customers in making informed purchasing decisions when comparing different Fisher & Paykel products. For example, a heat pump dryer typically has a lower In-use Energy Carbon Emissions Estimate than a vented dryer.



A PEACE OF MIND SALE
24 Hours 7 Days a Week Customer Support
T 1.888.936.7872 W www.fisherpaykel.com