
QUICK REFERENCE GUIDE > CDV2-365HL N Date: 04.04.2024 > 1

Gas Cooktop, 36", LPG

Series 9 | Professional

Stainless Steel | LPG




A powerful high-heat five burner with precision control and performance. Pair with any other appliance in our Professional range.

- Your burners can deliver anything from a high 20,000 BTU heat per burner for fast boiling, to a gentle flame for simmering
- Continuous surface grates designed for pots and pans to move safely across the cooktop

DIMENSIONS

Height	5 1/2"
Width	36"
Depth	21"



FEATURES & BENEFITS

Perfect heat

Sealed Dual Flow Burners™ deliver cooktop power up to 20,000 BTU for seriously fast boiling right down to a precise 140°F full surface simmer with the gentlest of flames.

Precise control

From the highest to the lowest temperatures you get total control with halo-illuminated cooktop dials. A precise full surface simmer is delivered across all burners.

Information at a glance

LED halo control dials provide information at a glance and assist in alerting you if any burners are accidentally left on.

Cooking flexibility

The self-locating grates focus the flame on the base of each pan, where it is most required. They are designed for easy and safe sliding of pans across the cooktop surface. For cooking variety, a wok ring accessory is also available.

Easy cleaning

These cooktops have sealed burners and a single sheet cooking surface which, combined with a commercial-style stainless steel finish and dishwasher-safe grates, allow easy cleaning.

Complementary design

Built to last with distinctive, bold styling, this cooktop is designed to match the Fisher & Paykel Professional style family of appliances.

SPECIFICATIONS

Burner ratings	
Max burner power	Yes
Power back left	12000BTU
Power back right	12000BTU
Power front centre	20000BTU
Power front left	12000BTU
Power front right	12000BTU

Controls

Metal illuminated dials

Performance

Sealed Dual Flow Burners™ 5
Simmer on all burners 140°F

QUICK REFERENCE GUIDE > CDV2-365HL N Date: 04.04.2024 > 2

Power requirements	
Amperage	15A
Supply frequency	60Hz
Supply voltage	120V
Product dimensions	
Depth	21"
Height	5 1/2"
Width	36"
Recommended Back Guards Ventilation	
Minimum CFM	600 BTU
Pro hood	VS36

The product dimensions and specifications in this page apply to the specific product
and model. Under our policy of continuous improvement, these dimensions and
specifications may change at any time. You should therefore check with Fisher &
Paykel's Customer Care Centre to ensure this page correctly describes the model

currently available. ? Fisher & Paykel Appliances Ltd 2020

Warranty

SKU

Parts and labour

Other product downloads available at fisherpaykel.com



Service & Warranty



User Guide EN / Guide d'utilisation FR



Installation Guide EN / Guide d'installation FR



Data Sheet Gas Cooktop



2 years

71397

A PEACE OF MIND SALE

24 Hours 7 Days a Week Customer Support

T 1.888.936.7872 **W**www.fisherpaykel.com