QUICK REFERENCE GUIDE > HP60IDCHEX3

Integrated Insert Rangehood, 60cm, with External Motor

Series 7 | Integrated

Stainless Steel and Glass



Seamlessly fits in cabinetry above your cooktop, with an external motor for near silent yet powerful extraction in the kitchen.

- External motor delivers near silent operation in the kitchen
- With three fan speeds plus a boost function, select the perfect extraction rate for your cooking
- Powerful 1200m3/h maximum airflow
- Dimmable LED strip lighting illuminates the cooking surface beautifully

DIMENSIONS

Height 315mm
Width 530mm
Depth 280mm

FEATURES & BENEFITS

Near Silent Extraction

The powerful external motor is installed outside the home to deliver near silent extraction of cooking odours and steam from the kitchen.

Seamless Integration

This rangehood can be built into your cabinetry for a seamless look. Its black glass control panel and stainless steel finish is designed to match the rest of Fisher & Paykel's kitchen appliance family.

Effective Extraction

This rangehood features three fan speeds plus boost function, providing powerful extraction to quickly remove odours and steam. As odours can linger in the kitchen well after cooking is finished, the timer keeps the rangehood running before automatically turning off.

Full surface lighting

Low energy, dimmable LED lights provide superb illumination over the entire cooking surface.

Easy To Use

This Fisher & Paykel rangehood features a sleek and easy to use touch-control panel.

Easy cleaning

The glass and stainless steel finishes are easily wiped clean and the filters are simple to clean and dishwasher safe. An alert reminds you when to clean the filter and ensures you get the best performance out of your rangehood.

Considered Efficiency

The four speeds with a range of different airflows means you can effectively remove cooking odours with reduced effect on your heating or air conditioning, ensuring less energy is used.

SPECIFICATIONS

Accessories	
Aluminium filter	792942
External motor kit	50170 HB 1200E* (included)
Accessories (sold separately)	
Extra ducting length	792961
Light bulb	requires service to replace
Fan ratings	
Maximum air movement	1200m³/hr

Maximum pressured air 820m³/hr Speed 1 sound rating 40dBA

Installation and cleaning Dishwasher safe filters

Ducted	Top extraction

Stainless steel filter cover

Extraction type Perimeter Fan speeds 4

Number of filters

Power requirements

Performance

QUICK REFERENCE GUIDE > HP60IDCHEX3

Supply frequency	50Hz
Supply voltage	240V
Product dimensions	
Depth	280mm
Height	315mm
Width	530mm
Product information	
Control type	Capacitive touch
Ventilation features	
Dimmable lights	•
Filter cleaning alert	•
Light type	LED strip
Timer function	•
Warranty	
Parts and labour	2 years

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. ? Fisher & Paykel Appliances Ltd 2020

SKU

Other product downloads available at fisherpaykel.com



Service & Warranty



User Guide Integrated Insert Rangehood with External Blower



Installation Guide Integrated Insert Rangehood with External Blower



50166

Installation Guide Rangehood External Blower



A PEACE OF MIND SALE

24 Hours 7 Days a Week Customer Support

T 1300 650 590 Wwww.fisherpaykel.com