

76cm Series 9 Professional Warming Drawer

Professional



Keep plates warm until ready to serve, Rapid Proof or Slow Cook. Pair with a Professional style oven for design cohesion.

- A companion product, designed to match other Professional style Fisher & Paykel products
- Space to keep 16 standard-sized place settings evenly warm, with an accessory rack for optimising space
- Easy to clean smooth glass base
- Six versatile tailored programs for warming, proofing, dehydrating and slow cooking

DIMENSIONS

Height	271 mm
Width	761 mm
Depth	568 mm

FEATURES & BENEFITS

- Complementary Design**
Our Warming Drawer comes in brushed stainless steel, for seamless pairing with our matching Professional style ovens.
- Multi-Function Flexibility**
Choose from six tailored functions including Rapid Proof, Dehydrate and Slow Cook.
- Easy To Clean**
Cleaning the Warming Drawer is simple. After each use, just wipe out the smooth glass interior with a damp cloth.
- Easy To Use**
Soft-close with capacitive touch controls, this Warming Drawer comes with an accessory rack for optimising space.
- Precise Control**
With fast and even heating, this Warming Drawer is great for quickly proofing dough, low temperature cooking, resting meats or keeping dishes warm.
- Safe And Sound**
With automatic switch-off and Delayed Start functionality, our Warming Drawers help keep dishes warm until it is time to serve.

SPECIFICATIONS

Accessories (included)	
Wire shelf	1
Capacity	

Accessory rack maximum allowable weight	42lbs
Cappuccino cups	24
Espresso cups	54
Place settings	16

Cleaning	
Easy clean smooth-glass base	•
Controls	
Audio feedback	•
Automatic timers	30', 45', 1h, 2h, 4h, 6h
Delayed start	•
Electronic capacitive touch controls	•
LED lights	1
On/Off indicator	•
Pre-set heating functions	•
Standby mode	•
Functions	
Cups	•
Dehydrate	•
Plates	•
Rapid proof	•
Slow cook	•
Warm	•
Performance	
Heated glass base and fan	•
Low temperature cooking	•

Temperature levels 6

Power requirements

Amperage 10 A
Power cord length 1800 mm
Power outlet Flex cord
Supply frequency 60 Hz
Supply voltage 220-240 V

Product dimensions

Adjustable front door panel to align with surrounding cabinetry •
Depth 568 mm
Height 271 mm
Width 761 mm

Safety

Automatic turn off after 12 hours •
Full extension slides •

SKU 82726

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. © Fisher & Paykel Appliances Ltd 2020

Other product downloads available at fisherpaykel.com

- ↓ DXF
- ↓ Archicad
- ↓ DWG
- ↓ Installation Guide (English)
- ↓ Planning Guide - Professional 76cm Built-in Ovens and Companions (English)
- ↓ Revit
- ↓ SketchUp
- ↓ User Guide (English)

Where applicable:

All appliances use energy, and energy usage typically generates carbon emissions. Fisher & Paykel Appliances' In-use Energy Carbon Emissions Estimate indicates carbon emissions from a product's in-use energy. This is calculated either annually or per cycle, using the product's market-specific energy label energy consumption data multiplied by the carbon emissions factor for energy in your country or region.

Our In-use Energy Carbon Emissions Estimate is designed to assist customers in making informed purchasing decisions when comparing different Fisher & Paykel products. For example, a heat pump dryer typically has a lower In-use Energy Carbon Emissions Estimate than a vented dryer.



A PEACE OF MIND SALE
24 Hours 7 Days a Week Customer Support
T 1300 650 590 W www.fisherpaykel.com