Gas Rangetop, 48", LPG

Series 9 | Professional

Stainless Steel | LPG



Eight burners for when you need maximum performance and cooktop space - great for those who love to cook for a crowd.

- Your burners can deliver anything from very high 19,000 BTU heat for seriously fast boiling, to the most gentle flame for simmering
- Continuous surface grates designed for pots and pans to move safely across the cooktop
- Designed to match Professional style appliances
- Made from guality materials and real stainless steel

DIMENSIONS

Height	8 5/16″
Width	47 7/8"
Depth	28″

FEATURES & BENEFITS

Cooktop power

Sealed Dual Flow Burners[™] deliver rangetop power up to 19,000 BTU for seriously fast boiling right down to a precise 140°F full surface simmer with the gentlest of flames.

Precise control

From the highest to the lowest temperatures you get total control with halo-illuminated rangetop dials. A precise full surface simmer is delivered across all burners.

Precise control

From the highest to the lowest temperatures you get total control with halo-illuminated rangetop dials. A precise full surface simmer is delivered across all burners.

Cooking flexibility

The continuous surface grates are designed for pots and pans to move safely across the rangetop. The deep-platform style grates provide full coverage so heat goes directly onto the pot, for a faster boil.

Easy to clean

These rangetops are easy to clean with sealed burners and a continuous, porcelain basepan.

Information at a glance

LED halo control dials provide information at a glance and assist in alerting you if any burners are accidentally left on.

Design quality

This rangetop is built to last with craftsmanship in every detail, featuring real stainless steel, cast-iron grates, and titanium coated dials.

FISHER & PAYKEL

SPECIFICATIONS

Burner ratings	
Max burner power	Yes
Power back centre	13,000 BTU
Power back centre (2)	13,000 BTU
Power back left	13,000 BTU
Power back right	13,000 BTU
Power front centre	15,000 BTU
Power front centre (2)	15,000 BTU
Power front left	19,000 BTU
Power front right	19,000 BTU
Total cooktop power	120,000 BTU

Cleaning

Easy clean porcelain basepan

Controls

Metal illuminated dials	•
Star K Certification	•
Titanium coated, illuminated	•

Gas Requirements

Fitting and pipe	½ NPT, min. 5%" 🛛 flex line
Supply Pressure (LPG)	11" to 14" W.C

Performance

Sealed Dual Flow Burners™	8
Sealed cooking surface	•

QUICK REFERENCE GUIDE > CPV3-488-L

Simmer on all burners	140°F
Power requirements	
Amperage	15A
Supply frequency	60Hz
Supply voltage	120V
Product dimensions	
Depth	28″
Height	8 5/16″
Width	47 7/8″
Recommended Back Guards	Ventilation
Combustible situation	BGCV2-3048H
Non combustible situation	BGCV2-3048 / BGCV2-1248
Pro hood	HCB48-12_N

Other product downloads available at fisherpaykel.com ≁ User Guide ↓ Guide d'utilisation FR ↓ Service & Warranty ≁ Installation Guide EN ↓ Guide d'installation FR ↓ Data Sheet Gas Rangetop and Low Backguard ≁ Data Sheet Gas Rangetop ↓ Data Sheet Gas Rangetop and Low Shelf High Backguard ↓ Data Sheet Gas Rangetop and High Shelf High Backguard

Planning Guide Professional Style Dial/Handle Accessories

Safety

ADA compliant

Warranty		
Parts and labour	2 years	
SKU	82009	

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. ? Fisher & Paykel Appliances Ltd 2020

A PEACE OF MIND SALE

24/7

24 Hours 7 Days a Week Customer Support

T 1.888.936.7872 Wwww.fisherpaykel.com